

Oil sep. NS3 with Bypass and ACD

class I

H1	1090
H2	652
H3	1020
H4 a	811
b	911
c	1011
D1	$\phi 1427$
D2	$\phi 200$
L1	3269
L2	1174
L3	1186

Oil sep. NS3 with Bypass and ACD

class II

H1	1090
H2	652
H3	1020
H4 a	811
b	911
c	1011
D1	$\phi 1427$
D2	$\phi 200$
L1	3269
L2	1174
L3	1186

Volume and capacity

Nominal size	NS3 class I	NS3 class II
Effective volume	2557 l	2595 l
Oil storage capacity	350 l	>350 l
Effective volume sludge trap	~	~
Max flow rate oil sep	3 l/s	3 l/s
Max flow rate bypass	27 l/s	27 l/s

Part List

1	Inlet pipe	
2	Bypass	
3	Level sensors	(Optional)
4	Oil skimming pipe $\phi 160$	
5	Maintenance shaft	
6	Filter blocks	
7	Automatic closure device (ACD)	(Optional)
8	Outlet pipe	


REV.5	REV.6
REV.3	REV.4
REV.1	REV.2

Status:



BELONGS TO DWG  
PART OF DWG

AMERICAN PROJECTION



NAME : Oil separator NS3 with bypass

DATE : 1-12-2009

SCALE : UNITS MM

DRAWN : M. Schouten

PIPELIFE CORPORATE R&D, FLEVOLAAN 7 1601 MA ENKHUIZEN, THE NETHERLANDS

DWG NO : 046-011367

A4