

Oil sep. NS3 with sludge trap, bypass and ACD

class I

Oil sep. NS3 with sludge trap, bypass and ACD

class II

H1	1372	1372
H2	652	652
H3	1272	1272
H4 a	846	846
b	946	946
c	1046	1046
D1	ø1720	ø1720
D2	ø200	ø200
L1	3905	3905
L2	1298	1298
L3	1647	1647

Volume and capacity

Nominal size	NS3 class I	NS3 class II
Effective volume	3766 L	3784 L
Oil storage capacity	>400 L	>400 L
Effective volume sludge trap	>1200 L	>1200 L
Max flow rate oil sep	3 l/s	3 l/s
Max flow rate bypass	27 l/s	27 l/s

Part list

1	Inlet pipe	
2	Bypass	
3	Separation plate Sludge trap	
4	Level sensors	(Optional)
5	Oil skimming pipe ø160	
6	Maintenance shaft	
7	Filter blocks	
8	Automatic closure device (ACD)	(Optional)
9	Outlet pipe	

GEW.5	GEW.6
GEW.3	GEW.4
GEW.1	GEW.2


Status:



BEHOORT BIJ TEK.

AMERIKAANSE PROJECTIE

BIJBEHORENDE TEK.



BENAMING : Oil separator NS3 with sludge trap and bypass

DATUM : 1-12-2009

SCHAAL : UNITS MM

GETEK. : M. Schouten

PIPELIFE NEDERLAND B.V. POSTBUS 380 1600 AJ ENKHUIZEN

TEL: 0228-355555 TELEFAX 0228-355666

TEK.NR. : 046-011369

A4