

Oil sep. NS6 with Bypass and ACD

class I

Oil sep. NS6 with Bypass and ACD

class II

H1	1060	1060
H2	753	753
H3	990	990
H4 a	841	841
b	941	941
c	1041	1041
D1	$\phi 1427$	$\phi 1427$
D2	$\phi 250$	$\phi 250$
L1	3289	3289
L2	1184	1184
L3	1196	1196

Volume and capacity

Nominal size	NS6 <i>class I</i>	NS6 <i>class II</i>
Effective volume	2525 l	2595 l
Oil storage capacity	350 l	>350 l
Effective volume sludge trap	~	~
Max flow rate oil sep	6 l/s	6 l/s
Max flow rate bypass	54 l/s	54 l/s

Part List

1	Inlet pipe	
2	Bypass	
3	Level sensors	(Optional)
4	Oil skimming pipe $\phi 160$	
5	Maintenance shaft	
6	Filter blocks	
7	Automatic closure device (ACD)	(Optional)
8	Outlet pipe	

GEW.5	GEW.6
-------	-------

GEW.3	GEW.4
-------	-------

GEW.1	GEW.2
-------	-------


Status:



BEHOORT BIJ TEK.

AMERIKAANSE PROJECTIE

BIJBEHORENDE TEK.



BENAMING : Oil separator NS6 with bypass

DATUM : 1-12-2009

SCHAAL : UNITS MM

GETEK. : M. Schouten

PIPELIFE NEDERLAND B.V. POSTBUS 380 1600 AJ ENKHUIZEN TEL: 0228-355555 TELEFAX 0228-355666

TEK.NR. : 046-011371

A4