



Oil sep. NS6 with sludge trap, bypass and ACD

class I

Oil sep. NS6 with sludge trap, bypass and ACD

class II

H1	1342	1342
H2	753	753
H3	1242	1242
H4 a	876	876
b	976	976
c	1076	1076
D1	Ø1720	Ø1720
D2	Ø250	Ø250
L1	3925	3925
L2	1309	1309
L3	1657	1657

Volume and capacity

Nominal size	NS6 class I	NS6 class II
Effective volume	3712 l	3784 l
Oil storage capacity	>400 l	>400 l
Effective volume sludge trap	>1200 l	>1200 l
Max flow rate oil sep	6 l/s	6 l/s
Max flow rate bypass	54 l/s	54 l/s

Part list

1	Inlet pipe	
2	Bypass	
3	Separation plate Sludge trap	
4	Level sensors	(Optional)
5	Oil skimming pipe Ø160	
6	Maintenance shaft	
7	Filter blocks	
8	Automatic closure device (ACD)	(Optional)
9	Outlet pipe	

GEW.5 GEW.6

GEW.3 GEW.4

GEW.1 GEW.2

Status:



BEHOORT BIJ TEK.

AMERIKAANSE PROJECTIE

BIJBEHORENDE TEK.



BENAMING : Oil separator NS6 with sludge trap and bypass

DATUM : 1-12-2009

SCHAAL : UNITS MM

GETEK. : M. Schouten

PIPELIFE NEDERLAND B.V. POSTBUS 380 1600 AJ ENKHUIZEN TEL: 0228-355555 TELEFAX 0228-355666

TEK.NR. : 046-011373

A4