

Oil sep. NS6 with sludge trap and ACD

class I

Oil sep. NS6 with sludge trap and ACD

class II

H1	1469	1469
H2	391	391
H3	1369	1369
H4		
a	749	749
b	849	849
c	949	949
D1	1720	1720
D2	125	125
L1	3030	3030
L2	834	834
L3	1237	1237

Volume and capacity

Nominal size	NS6 class I	NS6 class II
Effective volume	3712 l	3784 l
Oil storage capacity	>400 l	>400 l
Effective volume sludge trap	>1200 l	>1200 l
Max flow rate oil sep	6 l/s	6 l/s
Max flow rate bypass	~	~

Part list

1	Inlet pipe	
2	Separation plate Sludge trap	
3	Level sensors	(Optional)
4	Oil skimming pipe $\phi 160$	
5	Maintenance shaft	
6	Filter blocks	
7	Outlet pipe with optional ACD (Automatic Closure Device)	

REV.5	REV.6
REV.3	REV.4
REV.1	REV.2


Status:



BELONGS TO DWG

AMERICAN PROJECTION

PART OF DWG



NAME : Oil separator NS6 with sludge trap

DATE : 1-12-2009

SCALE : UNITS MM

DRAWN : M. Schouten

PIPELIFE CORPORATE R&D, FLEVOLAAN 7 1601 MA ENKHUIZEN, THE NETHERLANDS

DWG NO : 046-011372 A4