

WE HAVE A NAME FOR SPEEDY CIRCUIT  
AND CABLE FEEDING!

# TOPSPEED PLUS

ALL ABOUT THE NEW CONDUIT TYPES  
WITH HIGH SLIDING INNER SURFACES **PLUS TAUT WIRES!**



# NEWS FROM PIPELIFE!

## Fast, faster, TOPSPEED PLUS!

### A "plus" of time saving by pre-installed taut wire.

Because of the high sliding inner surface conduits and cables can be installed much easier and faster – and therefore more economical. In addition to that we now offer the **taut wired conduits** that reduce the time for installation even more.

#### **FB-E-LF TOPSPEED PLUS (classification 22322)**

The flexible PVC conduit made from Polyolefin with low pressure resistance (320 N/5 cm) and impact strength. Noncorrosive, temperature resistant from -15 °C to +90 °C, flame-retardant, self-extinguishing. Can be used for all installations (in, on and under walls as well as for cavity wall installation). Available in dimensions of 20 and 25 mm.

#### **RP-E-MF TOPSPEED PLUS (classification 33412)**

The flexible armoured conduit made from PVC-U (core) and liner from PVC-P with medium pressure resistance (750 N/5 cm) and impact strength. Noncorrosive, temperature resistant from -25 °C to +60 °C, flame-retardant, self-extinguishing. Can be used for concrete installations (poured concrete, jolted concrete, compressed concrete) in, under, on walls as well as for cavity wall installation. Available in dimensions of 20 to 50 mm.

### Fast feeding with TOPSPEED PLUS means saving energy and time!



**"Electro installation conduits or closed electro installation circuits within construction parts need to be completely installed for each electric circuit before conduits or cables can be installed."**  
(resource: DN VDE 0100-520)

**Pipelife TOPSPEED PLUS conduits with ready installed taut wires correspond to the requirements of DIN VDE 0100-520, item 522.8.1.1.**

**Installation test** with NYM conduit 3 x 1,5 mm and conduit type FB-E-LF TOPSPEED of dimension M20 over a distance of 7 m with four 90° bends gave the following results:

|   |              |  |
|---|--------------|--|
| <b>Installation of the conduit</b>            | <b>→</b>     | <b>within 1:45 min. with high effort</b>   |
| <b>With installation aid (Kati-Blitz)</b>     | <b>→ →</b>   | <b>easily possible within 1:30 min.</b>    |
| <b>TOPSPEED PLUS with installed taut wire</b> | <b>→ → →</b> | <b>very fast and easy within 0:35 min.</b> |

**Result: compared to standard installation methods and installation aids the installation time can be reduced to about one third of the usual time when using our TOPSPEED PLUS with pre-installed taut wires.**



Pipelife Deutschland GmbH & Co. KG Bad Zwischenahn

Postfach 1454 · D-26149 Bad Zwischenahn · Steinfeld 40 · D-26160 Bad Zwischenahn  
Tel. 0 44 03/6 05-0 · Fax 0 44 03/6 05 656 · E-Mail: info@pipelife.de · www.pipelife.de